

F0810

Date 06-05-19  
Page 1/1

## Inspection Certificate Acc. EN 10204-3.1

Item No.: 24476102

Product: POLYWHITE P 8555

Lot number: 9E232378DA

WHITE

ASBAG 25

Characteristic / Method	Unit	LSL	USL	Mean Value	DEV
MFR 230°C / 2,16 Kg DIN EN ISO 1133	g/10'	*	*	22,0	0,846069
MVR 230°C / 2,16 Kg DIN EN ISO 1133	cm³/10'	14,0	24,0	16,6	0,639661
ASH at 600°C DIN EN ISO 1172	%	53,0	57,0	55,3	0,408656
BULK DENSITY DIN EN ISO 60	Kg/m³	800	1000	966	8,94427
MOISTURE DIN EN ISO 760	ppm	0	1500	224	12,5897
DISPERSION at 20 % AS-R04	P/10g Film	0	10	1	0,447214
COLOUR ( Visual check ) AS-T00	Attribute.	---	---	OK	
DELTA E (D65) CIELAB / ASTM E 308		0,0	1,0	0,3	0,057735
CONTAMINATION AS-V00	Attribute.	---	---	OK	
PELLET APPEARANCE AS-V06	Attribute.	---	---	OK	
Pellet shape SPHERICAL					

\* = LSL and USL are temporary not available

Inspection Representative

This document is generated electronically and is valid without signature.

The material covered by this delivery is produced in accordance with A.Schulman's manufacturing specifications currently in force for this product grade. A.Schulman certifies that the material supplied conforms to the performance typical for this grade and product description, and has been monitored in accordance with the internal quality control routines employed in our company. However, the buyer must check the suitability of this grade for the actual application. Our general conditions of sale remain in force.