

**PRODUCT CHARACTERISTICS:**

<b>PROPERTIES</b>	<b>METHOD</b>	<b>UNIT</b>	<b>COMMENT</b>	<b>NOMINAL VALUES</b>	
				<b>MIN</b>	<b>MAX</b>
<b>Color</b>			Black/ Grey		
<b>Melt Flow Index</b>	ISO1133	g/10min	190°C / 2,16kg	<b>0,07</b>	<b>0,12</b>
<b>Melt Flow Index</b>	ISO1133	g/10min	190°C / 5,0kg	<b>0,40</b>	<b>0,60</b>
<b>Melt Flow Index</b>	ISO1133	g/10min	190°C / 21,6kg	<b>11,00</b>	<b>14,00</b>
<b>Izod Impact - Notched @ 23 °C</b>	ISO180	J/m <sup>2</sup>		<b>&gt;20</b>	
<b>Density</b>	ISO1183-1	g/cm <sup>3</sup>	23 °C	<b>0,946</b>	<b>0,955</b>
<b>Moisture Content</b>	-	% w/w	2 min @ 120°C	-	<b>&lt;0,15</b>
<b>Tensile strength</b>	ISO 527	Mpa	23°C 50mm/min	<b>20</b>	<b>30</b>
<b>E- Modulus</b>	ISO 527	Mpa	23°C 1mm/min	<b>&gt;700</b>	
<b>OIT</b>	ASTM D3895	min		<b>&gt;50</b>	