

TYRIL™ 905UV SAN Resin

Overview

TYRIL* styrene-acrylonitrile (SAN) resins are designed by Styron to offer superior chemical resistance, strength, hardness and dimensional stability in a broad range of product applications. The key property of TYRIL 905 is its superior water-clear clarity compared to other SAN resins and a high thermal stability that results in consistent color (reduced yellowing). TYRIL 905 is designed for applications demanding chemical and heat resistance and offers good processability. TYRIL 905 represents a technology breakthrough in trace-color reduction. Its thermal stability and exceptionally low base color make it a product especially suited for self-coloring. The UV-stabilized version exhibits excellent weather ability, suitable in particular for lighting applications.

Applications:

- Large appliances: transparent refrigerator parts
- Lighting applications: louvers and covers
- Automotive: taillight lenses and reflectors
- Cosmetic packaging: water-clear, thick-wall applications

Physical	Nominal Value (English)	Nominal Value (SI)	Test Method
Density	1.08 g/cm ³	1.08 g/cm ³	ASTM D792 ISO 1183/B
Apparent Density	0.69 g/cm ³	0.69 g/cm ³	ASTM D1895 ISO 60
Melt Mass-Flow Rate (MFR)			ASTM D1238 ISO 1133
220°C/10.0 kg	13 g/10 min	13 g/10 min	
230°C/3.8 kg	5.0 g/10 min	5.0 g/10 min	
Mechanical	Nominal Value (English)	Nominal Value (SI)	Test Method
Tensile Modulus	522000 psi	3600 MPa	ASTM D638 ISO 527-2
Tensile Strength (Break)	9860 psi	68.0 MPa	ISO 527-2/5 ASTM D638 ¹
Flexural Strength	13800 psi	95.0 MPa	ASTM D790 ISO 178
Impact	Nominal Value (English)	Nominal Value (SI)	Test Method
Charpy Unnotched Impact Strength			ISO 179
73°F (23°C)	7.1 ft-lb/in ²	15 kJ/m ²	
Unnotched Izod Impact Strength (73°F (23°C))	5.7 ft-lb/in ²	12 kJ/m ²	ISO 180
Hardness	Nominal Value (English)	Nominal Value (SI)	Test Method
Rockwell Hardness (M-Scale)	82	82	ASTM D785 ISO 2039-2
Thermal	Nominal Value (English)	Nominal Value (SI)	Test Method
Deflection Temperature Under Load			ASTM D648 ISO 75-2/A
264 psi (1.8 MPa), Annealed	212 °F	100 °C	
Vicat Softening Temperature			
--	214 °F	101 °C	ASTM D1525 ² ISO 306/B50 ²
--	230 °F	110 °C	ASTM D1525 ³ ISO 306/A120 ³
CLTE - Flow	0.000028 in/in/°F	0.000050 cm/cm/°C	DIN 53752
Specific Heat	0.330 Btu/lb/°F	1380 J/kg/°C	ASTM D2766
Electrical	Nominal Value (English)	Nominal Value (SI)	Test Method
Relative Permittivity (1 MHz)	3.00	3.00	IEC 60250
Dissipation Factor (1 MHz)	0.00010	0.00010	IEC 60250
Electric Strength	230 V/mil	9.1 kV/mm	IEC 60243-1

Flammability	Nominal Value (English)	Nominal Value (SI)	Test Method
Flame Rating - UL (0.0630 in (1.60 mm))	HB	HB	UL 94 ⁴

Notes

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

¹ 0.20 in/min (5.0 mm/min)

² Rate A (50°C/h), Loading 2 (50 N)

³ Rate B (120°C/h), Loading 1 (10 N)

⁴ This rating not intended to reflect hazards presented by this or any other material under actual fire conditions.

Product Stewardship

Styron LLC, Styron HoldCo B.V., and subsidiaries (“Styron”) have a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Styron products ☒ from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Styron strongly encourages its customers to review both their manufacturing processes and their applications of Styron products from the standpoint of human health and environmental quality to ensure that Styron products are not used in ways for which they are not intended or tested. Styron personnel are available to answer your questions and to provide reasonable technical support. Styron product literature, including safety data sheets, should be consulted prior to use of Styron products. Current safety data sheets are available from Styron.

Medical Applications Policy

NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS: Styron will not knowingly sell or sample any product or service (“Product”) into any commercial or developmental application that is intended for:

- long-term or permanent contact with internal bodily fluids or tissues. “Long-term” is contact which exceeds 72 continuous hours;
- use in cardiac prosthetic devices regardless of the length of time involved (“cardiac prosthetic devices” include, but are not limited to, pacemaker leads and devices, artificial hearts, heart valves, intra-aortic balloons and control systems, and ventricular bypass-assisted devices);
- use as a critical component in medical devices that support or sustain human life; or
- use specifically by pregnant women or in applications designed specifically to promote or interfere with human reproduction.

Styron requests that customers considering use of Styron products in medical applications notify Styron so that appropriate assessments may be conducted. Styron does not endorse or claim suitability of its products for specific medical applications. It is the responsibility of the medical device or pharmaceutical manufacturer to determine that the Styron product is safe, lawful, and technically suitable for the intended use. **STYRON MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OF ANY STYRON PRODUCT FOR USE IN MEDICAL APPLICATIONS.**

Disclaimer

NOTICE: No freedom from infringement of any patent owned by Styron or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer’s use and for ensuring that the Customer’s workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Styron assumes no obligation or liability for the information in this document. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

NOTICE: If products are described as “experimental” or “developmental”: (1) product specifications may not be fully determined; (2) analysis of hazards and caution in handling and use are required; (3) there is greater potential for Styron to change specifications and/or discontinue production; and (4) although Styron may from time to time provide samples of such products, Styron is not obligated to supply or otherwise commercialize such products for any use or application whatsoever.

Responsible Care®

Our top priority is to provide the highest quality products and services, and to focus on the American Chemistry Council’s Responsible Care® initiative and safety in all of our facilities.

Additional Information

North America	Europe/Middle East	+800 444 11 444
U.S. & Canada:	1-888-STYRON1	+31-11567-2626
	1-989-633-1718	+8001811361
Mexico:	+1-800-441-4369	
Latin America	Asia Pacific	+800-7776-7776
Argentina:	+54-11-4319-0100	+603-7965-5319
Brazil:	+55-11-5188-9000	
Colombia:	+57-1-219-6000	
Mexico:	+52-55-5201-4700	

www.styron.com

This document is intended for use within Europe

Published: November 2011

© 2011 Styron LLC, Styron HoldCo B.V., and subsidiaries

