

Technical Specification Sheet

Printed Date: 12-01-2015

Revision Date: 12-01-2015

Revision No.: 0

Technical Specification

Product **214954** **POLYCOLOR P 405286/2NWS** **VIOLET** **ASBAG**
25

PROPERTY	UNIT	TEST METHOD	LIMITS
MOISTURE	ppm	DIN EN ISO 760	0.0000-1500.0000
DELTA E (D65)		CIELAB / ASTM E 308	0.0000-1.0000
# BASE RESIN		-	PP
# SPECIFIC GRAVITY	g/cm ³	Calculated value	1.0 +-2
# PELLET SHAPE		-	CYL/SPHER
# TOTAL PIGMENT CONTENT	%	Calculated value	14.6 +- 0.5
# PIGMENT TYPE (Organic / Inorganic)		-	INORG/ORG
# WEATHER FASTNESS	1 - 5	DIN54001	4 (at 2%)
# LIGHT FASTNESS	1 - 8	DIN53388	7 (at 2%)
# HEAT STABILITY (5' Dwell time)	°C	AS-N00	300 (at 2%)
# FOOD CONTACT APPROVAL		-	INFO ON REQUEST

Typical values not mentioned on the inspection certificates.

This document is generated electronically and is valid without signature.

The details above reflect the limits of our internal specification. They do not represent a warranty of specific properties for a defined purpose. We guarantee the contractual properties of our products only within the framework of our "General Terms of Sale". The processor is not released from his obligation to verify the incoming goods or to test and examine the products to ensure that they are suitable for the intended purpose. This material specification is for information only and may be subject to change without further notice.